



Pigments and Color Packs

Product Name

Color Packs

Manufactured by

AVM Industries, Inc.
8245 Remmet Ave, Canoga Park, CA 91304
888.414.1041 818.888.0050
www.avmindustries.com

Product Description

AVM's Color Packs are concentrated pigment packs sold separately to be added to AVM's Top Coat Sealer 4100 Clear-FP (for Pigment) and to AVM's Texture Clear-FP (for Pigment). These color packs may also be used to tint AVM's Base Coat 100 Clear-FP (for Pigment), AVM's Acripatch 5020 and AVM's Primer 100.

Packaging and Sizes

AVM's color packs come in two sizes. Pints and Quarts. The Pint size Color Packs are to be mixed with AVM's two gallon buckets and the Quart size Color Packs are to be mixed with AVM's five gallon buckets.

Where to Use

AVM's Color Packs are designed to be added to AVM's Top Coat Sealer 4100 Clear-FP (for Pigment) and to AVM's Texture Clear-FP (for pigment). These color packs may also be used to tint AVM's Base Coat 100 Clear-FP (for pigment), AVM's Acripatch 5020 and AVM's Primer 100.

Warranty

AVM's Color Packs are manufactured to the strictest quality control standards. AVM's Color Packs have a one year warranty in their sealed (un-opened) containers and when properly stored in accordance with AVM's published storage instructions.

Delivery, Storage, and Handling

- Delivery of all the Elasto Fiberdeck® 100 system materials to the job site must be in their original sealed containers and bags, with manufacturer's name and label intact.
- Handle and store containers and bags in accordance with printed instructions.
- Store at temperatures between 50°F and 90°F. Do not store materials in direct sunlight or where they may be damaged by water or rain. Bags must be kept dry!
- Keep all materials out of the reach of children.
- If irritation occurs during use, liberally flush affected areas with water. If irritation continues, see a physician immediately.
- Shelf life - One year from date of manufacture.

Project Conditions

- Do not add the pigment pack's contents into materials that are below 50°F, or above 90°F.
- Provide adequate ventilation during mixing.
- Warn personnel against hazards of materials to skin and eyes.
- Protect adjacent surfaces which could be damaged during mixing.

Mixing Instructions

The small (Pint Size) Color Packs are to be used with AVM's 2-gallon buckets.

The large (Quart Size) Color Packs are to be used with AVM's 5-gallon buckets.

- Mix the Top Coat Sealer 4100 Clear-FP for 1 minute with a drill and paddle before adding the pigment.
- Shake the Color Pack by hand for 30-60 seconds before use. (Make sure it's well mixed!)
- Add the contents of the Color Pack to the bucket and mix well for 1-2 additional minutes, until evenly mixed.

Do NOT add water or dilute in any way!

Follow the same Mixing Instructions above if using the Color Packs with Texture Clear-FP and other AVM products.

Installation

Refer to AVM System 100 Elasto Fiberdeck and Forevercoat Installation Instructions for details.

Clean Up

Tools may be cleaned with water before pigments/resins are dry.

Availability and Cost

Contact AVM Industries, your distributor, or your approved applicator for pricing and availability.

Technical Services

Technical services are available by contacting our offices at: **888.414.1041** or **818.888.0050** or visit **www.avmindustries.com**

Item/Component	Packaging	Approx. Shipping Weights	VOC
2-Gal Color Pack	6 Pint size plastic jars per box	1.3 lbs each / 8 Lbs per Box	0 Grams/Liter
5-Gal Color Pack	6 Quart size plastic jars per box	3.1 lbs each / 19 Lbs per Box	0 Grams/Liter

For the MSDS and other info, please visit our website at www.avmindustries.com

For a complete list of details in CAD or PDF, please visit our website at www.avmindustries.com.

AVM Industries, Inc.
8245 Remmet Ave, Canoga Park, CA 91304
888.414.1041 818.888.0050

Quality Waterproofing Products

www.avmindustries.com



The following coverages are based on controlled tests. Actual coverages may vary.

Materials	One Kit Makes	One Kit Covers at 1/8" Thick	One Kit Covers at 1/4" Thick	One Kit Covers at 1/2" Thick
AVM Crete 6400	4 Gallons of Mixed Product	40 Square Feet	20 Square Feet	10 Square Feet
Weight of 1 sq. ft. of Crete 6400 installed & cured		1 sq. ft. at 1/8" thick = -1.25 lbs.	1 sq. ft. at 1/4" thick = -2.50 lbs.	1 sq. ft. at 1/2" thick = -5.00 lbs.

Materials	Over Plywood	Over Concrete	Over Sheet Metal
AVM Primer 100 / Optional AVM Epoxy Primer 400	200-300 sq. ft./gal.	200-300 sq. ft./gal.	200-300 sq. ft./gal.
AVM Base Resin 100	40-50 sq. ft./gal.	40-50 sq. ft./gal.	40-50 sq. ft./gal.
AVM Mat 100 / Optional Mat 800	Allow 5%-10% waste	Allow 5%-10% waste	Allow 5%-10% waste
AVM Texture 100 Sprayed Sand Finish	40-60 sq. ft./gal.	40-60 sq. ft./gal.	40-60 sq. ft./gal.
AVM Texture 100 Sprayed Knock Down Finish	40-60 sq. ft./gal. depending on desired look	40-60 sq. ft./gal. depending on desired look	40-60 sq. ft./gal. depending on desired look
AVM Texture 100 Troweled Smooth	35 sq. ft./gal.	35 sq. ft./gal.	35 sq. ft./gal.
AVM Top Coat Sealer 1st coat	100-120 sq. ft./gal.	100-120 sq. ft./gal.	100-120 sq. ft./gal.
AVM Top Coat Sealer 2nd Coat	150 sq. ft./gal.	150 sq. ft./gal.	150 Sq. ft./gal.

Technical Data - AVM System 100	
Fire Rating	Class A + 1 Hour over 2x8" Joists
Weatherometer	No Cracking, Softening, Crazing
Wind Uplift (Tested/Approved)	135+ lbs./sq. ft., -227 MPH/90 MPH
Abrasion	4.58% (Pass)
Bond Strength (Once Cured)	134 PSI
Compressive Strength ASTM C39,C172,C192,C470	7 Days: 2500 PSI, 28 Days: 3700 PSI

General Data - AVM System 100	
Shelf Life: (Liquids)	One year in original unopened packaging.
Storage Conditions	Store dry at 50°-90°F. If frozen, discard
Cement Mixing Ratio	Pre-proportioned kit. 1-bag to 1-gal. additive
Cement Color	Gray
Base/Texture Colors	4 Standard and many Custom
Top Coat Colors	20 Standard colors Custom colors are available - Call for details.

Minimum Dry Thickness - Complete System: 0.310. (AVM Crete 6400 must be at least 0.250" thick when dry)

Item/Component	Packaging	Approx. Shipping Weights	VOC
AVM AcriPatch 5020	2.0/5.0 gal. pails	2.0/5.0 gal. 15/39 lbs.	46 Grams/Liter
AVM Aggregate 400	50 lb. bag	50 lbs./bag	
AVM Additive 7400	2.0/5.0 gal. pails	2.0/5.0 gal. 18/46 lbs.	6 Grams/Liter
AVM Metal Lath 2.5#	10 sheets/bundle	5 lbs./sheet	
AVM Mat 100 / AVM Mat 800	1750 sq. ft. roll / 1080 sq. ft. roll	82.1 lbs. / 22.6 lbs.	
AVM Primer 100	2.0/5.0 gal. pails	2.0/5.0 gal. 18/46 lbs.	93 Grams/Liter
AVM Epoxy Primer 400	1.25 gal. kit / 5.0 gal. kit	11.6 lbs. / 47.6 lbs.	0 Grams/Liter
AVM Base 100	2.0/5.0 gal. pails	2.0/5.0 gal. 18/46 lbs.	85 Grams/Liter
AVM Texture 100	2.0/5.0 gal. pails	2.0/5.0 gal. 23/56 lbs.	31 Grams/Liter
AVM Top Coat 4100/4150	2.0/5.0 gal. pails	19/47 lbs.	85/73 Grams/Liter

For a complete list of details in CAD or PDF, please visit our website at www.avmindustries.com.

AVM Industries, Inc.
8245 Remmet Ave, Canoga Park, CA 91304
888.414.1041 818.888.0050

Quality Waterproofing Products



www.avmindustries.com